


■ Tubo pieghevole in poliuretano

Polyurethane flexible conduit

PU (HB UL94) 5006



Tubi flessibili ondulati prodotti in poliuretano, dotati di eccezionale flessibilità, buone caratteristiche meccaniche anche alle basse temperature ed elevata resistenza all'abrasione; requisiti ideali in tutte le applicazioni per la protezione e l'isolamento delle installazioni elettriche.

Ottima resistenza ai microbi ed alla maggior parte delle sostanze chimiche come oli, benzine, grassi, acidi e solventi. Autoestinguenti, privi di sostanze alogene, silicone e cadmio.

Superfici interne ed esterne ondulate consentono un ottimo scorrimento dei cavi, notevolmente più agevole rispetto ai tubi flessibili in PVC.

Buona resistenza ai raggi UV.

- Standard
CEI EN 61386-1 e 61386-23, EN 60204
- Grado IP CEI EN 60529 IP68 / IP69K
- Classificazione IP CEI EN 61386 - - 5 4
- Autoestinguenza
Non propagante la fiamma CEI EN 61386 HB (UL 94)

Flexible corrugated polyurethane conduits, designed for optimum flexibility, and good mechanical characteristics also at low temperatures and high abrasion resistance; ideal requirements in all applications for the protection and insulation of electrical installations.

Excellent resistance to microbes and to most chemical substances such as oils, petrol, acids and solvents.

Self-extinguishing, halogen, silicone and cadmium-free.

Corrugated internal and external surfaces ensure an excellent sliding of the cables, significantly easier than with flexible PVC conduits.

The product offers good resistance against UV rays.

- Standard
IEC EN 61386-1, 61386-23 and EN 60204
- IP degree IEC EN 60529 IP68 / IP69K
- Classification IEC EN 61386 - - 5 4
- Self-extinguishing
No flame propagation (CEI EN 61386) HB (UL94)



Profilo fine Fine profile

CODICE NERO BLACK CODE	DIAM. NOMINALE NOMINAL DIAM. ø, mm	DIAMETRO INT. INT. DIAMETER ø d, mm	DIAMETRO EST. EXT. DIAMETER ø D, mm	RAGGIO CURVA RADIUS CURVE		CONFEZIONE PACKAGE m
				stat.	din./dyn.	
5006-07N	10	6,5	10,0	13	35	0,020
5006-10N	13	8,8	13,0	15	40	0,035
5006-12N	15,8	11,4	15,8	22	55	0,046



Profilo grosso Thick profile

CODICE NERO BLACK CODE	DIAM. NOMINALE NOMINAL DIAM. ø, mm	DIAMETRO INT. INT. DIAMETER ø d, mm	DIAMETRO EST. EXT. DIAMETER ø D, mm	RAGGIO CURVA RADIUS CURVE		CONFEZIONE PACKAGE m
				stat.	din./dyn.	
5006-17N	21,2	15,2	21,2	35	75	0,056
5006-23N	28,5	22,0	28,5	45	100	0,090
5006-29N	34,5	27,5	34,5	50	120	0,120
5006-36N	42,5	35,5	42,5	80	150	0,165
5006-48N	54,5	47,0	54,5	100	190	0,225