

Raccordi in poliammide Polyamide fittings

A gomito 90° filetto maschio plastico 5022 / 5020 Elbow 90° plastic male thread 5022 / 5020



Filettature

- Metrico ISO conforme CEI EN 60423
- PG secondo DIN 40430
- GAS cilindrico UNI ISO 228
- NPT conforme norme ANSI B2.1

Colore
Nero



Codici di riferimento
RQW IP68/IP69K
RQW1 IP66

Threads

- ISO metric compliant IEC EN 60423
- PG in accordance with DIN 40430
- UNI ISO 228 GAS cylindrical
- NPT in compliance with ANSI B2.1.

Colour
Black

Reference code
RQW IP68/IP69K
RQW1 IP66



RQW IP68/IP69K

UL 1696 CSA22.2
File n.E86359
DN 13- 54,5



RQW1 IP66

UL 1696 CSA22.2
File n.E86359
DN 13- 54,5



DIN 5510-2 (S1)



EN/IEC 61386-23



NF F 16-101/102
(I3/F2)



EN 45545-2

HL2



Filettatura Metrica Metric thread

CODICE IP66 IP66 CODE	CODICE IP68/IP69K IP68/IP69K CODE	DN ø	ø F	DIMENSIONI, mm DIMENSIONS, mm					Ø D	kg/100pz	CONFEZIONE PACKAGE pz pcs
				ø I	ø B	C	E	F			
5022-0710N	5022-0710N67	10,0	M 10 x 1,0	6	17	12	33,5	34,5	16	0,60	50
5022-0712N	5022-0712N67	13,0	M 12 x 1,5	8	20	10	36	34	20	0,76	50
5022-1016N	5022-1016N67	13,0	M 16 x 1,5	12	20	12	36	36,5	20	0,72	50
5022-1216N	5022-1216N67	15,8	M 16 x 1,5	12	23	12	42	40,5	24,5	1,08	50
5022-1220N	5022-1220N67	15,8	M 20 x 1,5	15,5	23	13	42	41,5	24,5	1,06	50
5022-1720N	5022-1720N67	21,2	M 20 x 1,5	14,8	29,5	13	50	49	27	2,00	50
5022-1725N	5022-1725N67	21,2	M 25 x 1,5	18	29,5	13	50	49	29,5	1,94	50
5022-2325N	5022-2325N67	28,5	M 25 x 1,5	18	37	13	57	57	34	3,12	25
5022-2332N	5022-2332N67	28,5	M 32 x 1,5	24	37	15	57	59	37	3,04	25
5022-2932N	5022-2932N67	34,5	M 32 x 1,5	24	44	15	67,5	65	43	4,08	10
5022-2940N	5022-2940N67	34,5	M 40 x 1,5	32	44	15	67,5	67	45	4,40	10
5022-3640N	5022-3640N67	42,5	M 40 x 1,5	32	52	15	83	72	51,5	7,00	10
5022-3650N	5022-3650N67	42,5	M 50 x 1,5	39	52	15,5	83	74,5	55	7,30	10
5022-4850N	5022-4850N67	54,5	M 50 x 1,5	39	64	15	94	84	64	11,4	5
5022-4863N	5022-4863N67	54,5	M 63 x 1,5	53	64	16	94	85,5	68	10,8	5

Filettatura PG PG thread

CODICE IP66 IP66 CODE	CODICE IP68/IP69K IP68/IP69K CODE	DN ø	ø F	ø I	DIMENSIONI, mm DIMENSIONS, mm					Ø D	kg/100pz	CONFEZIONE PACKAGE pz pcs
					ø B	C	E	F				
5020-0707N	5020-0707N67	10,0	7	7	17	9,5	34	33	16	0,56	50	
5020-1009N	5020-1009N67	13,0	9	12	20	10	37	34	20	0,68	50	
-	5020-1011N67	13,0	11	14	20	10	39	34	23	0,78	50	
-	5020-1013N67	15,8	13,5	15,5	20	10	41	35	25	0,86	50	
5020-1211N	5020-1211N67	15,8	11	15,5	23	10	42	37,5	24,5	1,00	50	
5020-1413N	5020-1413N67	18,5	13,5	13,5	26,5	13	46	47	27	1,40	50	
5020-1716N	5020-1716N67	21,2	16	18	29,5	13	50	48	27	1,80	50	
5020-2321N	5020-2321N67	28,5	21	24	37	13	58	56	34	2,84	25	
5020-2929N	5020-2929N67	28,5	29	32	44	15	67,5	65	43	4,20	10	
5020-3636N	5020-3636N67	34,5	36	36,5	52	15	83	72	51,5	7,20	10	
5020-4848N	5020-4848N67	34,5	48	48,5	64	16	96	84	65	10,2	5	

■ Raccordi in poliammide Polyamide fittings

A gomito 90° filetto maschio plastico **5021 / 5023**

Elbow fittings 90° plastic male thread **5021 / 5023**

Filettatura GAS ISO 228 GAS ISO 228 thread

CODICE IP68/IP69K IP68/IP69K CODE	DN ø	ø F	ø l	DIMENSIONI, mm DIMENSIONS, mm					ø D	kg/100pz	CONFEZIONE PACKAGE pz pcs
				ø B	C	E	F				
5021-10012N67	13,0	1/2"	15	20	14	40	40	27	0,98	50	
5021-12012N67	15,8	1/2"	15	23	14	42	43	27	1,12	50	
5021-17012N67	21,2	1/2"	15	29,5	13	51	49	27	2,00	50	
5021-23034N67	28,5	3/4"	20,5	37	13	57	57	34	3,00	25	
5021-29001N67	34,5	1"	25	44	16	67,5	66,5	43	4,90	10	
5021-36114N67	42,5	1"1/4	35	52	18	83	76	52	7,05	10	
5021-48002N67	54,5	2"	52	64	18	96	89,5	66	10,2	5	

Filettatura NPT NPT thread

CODICE IP68/IP69K IP68/IP69K CODE	DN ø	ø F	ø l	DIMENSIONI, mm DIMENSIONS, mm					ø D	kg/100pz	CONFEZIONE PACKAGE pz pcs
				ø B	C	E	F				
5023-07014N	10	1/4"	8,5	17	10	34	33	16	0,40	50	
5023-10014N	13	1/4"	10	20	10,5	36	35	20	0,60	50	
5023-12038N	15,8	3/8"	12,5	23	12	42	40,5	24,5	0,80	50	
5023-12012N	15,8	1/2"	16	26	11	42	40,5	26	1,10	50	
5023-21012N	21,2	1/2"	16	29,5	13	51	48,5	27	1,88	50	
5023-22034N	28,5	3/4"	21	37	14	57,5	57	34	3,04	25	
5023-28001N	34,5	1"	28	44	16	67,5	66	43	4,80	10	
5023-36114N	42,5	1"1/4	35	52	18	83	76	52	5,20	10	
5023-36112N	42,5	1"1/2	36,5	54	16,5	83	76	56	5,50	10	
5023-48112N	54,5	1"1/2	41	64	18	95	87	64,5	14,0	5	
5023-48002N	54,5	2"	52	66	21	100	90	65	14,8	5	