


Raccordi in poliammide

Polyamide fittings

Monopezzo

One-piece



UL 1696 CSA22.2
File n.E86359



Semplicità di montaggio, resistenza alle vibrazioni ed allo strappo, dimensioni contenute per installazione ravvicinata, accoppiamento con i tubi flessibili e prodotti a norme DIN. Autoestinguenti, privi di sostanze alogene, silicone e cadmio. Alta resistenza agli oli, benzine, acidi e solventi. Il collegamento raccordo-tubo si ottiene spingendo a fondo il tubo nel raccordo, la cui forma interna liscia e troncoconica, consente di ottenere un grado di tenuta IP66. Per il disinnesto è necessario l'utilizzo di un normale cacciavite.

Ease of installation, resistance to vibration and tear, compact size for easier close-range installation and coupling with conduit products according to DIN. Self-extinguishing, halogen, silicone and cadmium-free. High resistance to oils, petrol, acids and solvents. The connection fitting-conduit is obtained by pushing the pipe into the connector, whose inner shape smooth and truncated conical, allows to obtain a sealing degree IP66. For the disconnection of the coupling it is necessary to use an ordinary screwdriver.

Filettature

- Metrico ISO conforme CEI EN 60423
- PG secondo DIN 40430 a richiesta

Threads

- ISO metric compliant IEC EN 60423
- PG in accordance with DIN 40430

Colore

Nero

Colour

Black

Dritto 5012L

Straight 5012L



Codice di riferimento
RQLG1 IP65
Reference code
RQLG1 IP65

CODICE IP65 IP65 CODE	DIMENSIONI, mm DIMENSIONS, mm							CONFEZIONE PACKAGE pz pcs
	DN ø	ø F	ø l	ø B	C	D	CH	
5012L-0712N	10	M 12 x 1,5	7,0	17,0	11,0	34,5	16	100
5012L-1016N	13	M 16 x 1,5	10,0	20,0	11,0	37,0	18	100
5012L-1220N	15,8	M 20 x 1,5	12,5	24,0	11,0	39,0	22	100
5012L-1420N	18,5	M 20 x 1,5	14,0	26,0	13,0	40,0	27	100
5012L-1425N	18,5	M 25 x 1,5	14,0	26,0	13,0	40,0	27	100
5012L-1720N	21,2	M 20 x 1,5	14,0	29,5	13,0	45,5	27	100
5012L-1725N	21,2	M 25 x 1,5	14,0	29,5	13,0	45,5	27	100
5012L-2325N	28,5	M 25 x 1,5	18,8	36,0	13,0	49,0	35	50
5012L-2332N	28,5	M 32 x 1,5	18,8	36,0	13,0	49,0	35	50
5012L-2932N	34,5	M 32 x 1,5	26,0	44,0	15,0	54,0	43	50
5012L-2940N	34,5	M 40 x 1,5	26,0	44,0	15,0	54,0	43	50
5012L-3640N	42,5	M 40 x 1,5	35,0	52,0	16,0	61,0	53	25
5012L-3650N	42,5	M 50 x 1,5	35,0	52,0	16,0	61,0	53	25
5012L-4850N	54,5	M 50 x 1,5	45,0	64,0	16,0	68,0	66	25
5012L-4863N	54,5	M 63 x 1,5	45,0	64,0	16,0	68,0	66	25

Curvo a 90° 5029L

Elbow 90° 5029L



Codice di riferimento
RQLB1 IP65
Reference code
RQLB1 IP65

CODICE IP65 IP65 CODE	DIMENSIONI, mm DIMENSIONS, mm							CONFEZIONE PACKAGE pz pcs
	DN ø	ø F	ø l	ø B	C	D	CH	
5029L-1016N	13	M 16 x 1,5	10,0	20,0	11,0	47,0	18	50
5029L-1220N	15,8	M 20 x 1,5	12,5	24,0	11,0	52,0	22	50
5029L-1420N	18,5	M 20 x 1,5	14,0	26,0	13,0	55,5	27	50
5029L-1425N	18,5	M 25 x 1,5	14,0	26,0	13,0	55,5	27	50
5029L-1720N	21,2	M 20 x 1,5	14,0	29,5	13,0	54,2	27	50
5029L-1725N	21,2	M 25 x 1,5	14,0	29,5	13,0	54,2	27	50
5029L-2325N	28,5	M 25 x 1,5	18,8	36,0	13,0	66,7	35	25
5029L-2332N	28,5	M 32 x 1,5	18,8	36,0	13,0	66,7	35	25
5029L-2932N	34,5	M 32 x 1,5	26,0	44,0	15,0	71,0	43	10
5029L-2940N	34,5	M 40 x 1,5	26,0	44,0	15,0	71,0	43	10
5029L-3640N	42,5	M 40 x 1,5	35,0	52,0	16,0	81,5	53	10
5029L-3650N	42,5	M 50 x 1,5	35,0	52,0	16,0	81,5	53	10
5029L-4850N	54,5	M 50 x 1,5	45,0	64,0	16,0	94,8	66	5
5029L-4863N	54,5	M 63 x 1,5	45,0	64,0	16,0	94,8	66	5