

## ■ Raccordi in poliammide Polyamide fittings

Per sensori **5061 / 5062**

For sensors **5061 / 5062**

Prodotti in poliammide di alta qualità, autoestinguenti, sono utilizzati per il collegamento dei sensori con led luminosi. A tale scopo sono prodotti in poliammide trasparente.

La tenuta IP65 si ottiene inserendo una guarnizione O-ring nel primo solco dell'ondulazione del tubo flessibile. Il collegamento tra adattatore e tubo flessibile avviene mediante l'escursione assiale di un particolare anello che blocca il tubo all'interno del raccordo. Filettatura tipo Metrico ISO in conformità con le norme CEI EN 60423.

Made of high quality polyamide, self-extinguishing, are used to connect sensors with LEDs.



For this purpose these adapters are produced in transparent polyamide.

IP65 seal is obtained by inserting an O-ring in the first groove of the corrugation of flexible conduit.

The connection between the adapter and flexible conduit occurs by axial excursion of a particular ring that secures the conduit inside the connector.

Produced with Metric ISO thread in compliance with IEC EN 60423.

### Dritto Straight



CODICE CODE	DIAMETRO NOMINALE NOMINAL DIAMETER	DIMENSIONI, mm DIMENSIONS, mm		CONFEZIONE PACKAGE
		ø F	L	
5061-070838N	10	8 x 1	39	50
5061-070853N	10	8 x 1	53	50
5061-071238N	10	12 x 1	39	50
5061-071253N	10	12 x 1	53	50
5061-071853N	10	18 x 1	53	50
5061-073053N	10	30 x 1,5	53	50
5061-100865N	13	8 x 1	65	50
5061-101265N	13	12 x 1	65	50
5061-101865N	13	18 x 1	65	50
5061-103065N	13	30 x 1,5	65	50

### A 90° At 90°



CODICE CODE	DIAMETRO NOMINALE NOMINAL DIAMETER	DIMENSIONI, mm DIMENSIONS, mm		CONFEZIONE PACKAGE
		ø F	L	
5062-070846N	10	8 x 1	46	50
5062-070860N	10	8 x 1	60	50
5062-071246N	10	12 x 1	46	50
5062-071260N	10	12 x 1	60	50
5062-071860N	10	18 x 1	60	50
5062-073060N	10	30 x 1,5	60	50