



# Pressacavo Cable gland

In ottone nichelato **6018**  
Nickel plated brass **6018**



Prodotti in ottone nichelato, sono composti da un corpo al cui interno alloggia un gommino in neoprene che si deforma sotto l'azione di un dado di serraggio, garantendo una tenuta stagna IP54 ed una buona tenuta allo strappo.  
Le guarnizioni sono resistenti all'invecchiamento, alla corrosione, agli oli e sono inerti nei confronti dei materiali che rivestono i cavi.

Made of nickel-plated brass, consists of a body, inside of which there is a neoprene rubber that deforms under the action of a tightening nut, ensuring a hermetic IP54 seal and a good tearing resistance.  
The seals are resistant to ageing, corrosion, oils and, remain inert to the material that sheaths the cables.



IP54

## Filettatura Metrica Metric thread

Conforme alle norme CEI EN 62444  
Complying with standards IEC EN 62444

| CODICE<br>CODE | SERRAGGIO CAVO<br>CABLE TIGHTENING<br>Ø Min - Ø Max | F       | DIMENSIONI mm<br>DIMENSIONS mm |     | LF   | CONFEZIONE<br>PACKAGE<br>pz / pcs. |
|----------------|---|---------|--------------------------------|-----|------|------------------------------------|
|                |   |         | CH1                            | CH2 |      |                                    |
| 6018-12A       | 4 ÷ 6   | M12x1,5 | 14                             | 13  | 5,0  | 50                                 |
| 6018-16        | 8 ÷ 10  | M16x1,5 | 17                             | 15  | 6,0  | 10                                 |
| 6018-20        | 10 ÷ 12   | M20x1,5 | 22                             | 20  | 7,0  | 20                                 |
| 6018-25        | 17 ÷ 19   | M25x1,5 | 30                             | 28  | 8,5  | 20                                 |
| 6018-32        | 19 ÷ 22   | M32x1,5 | 35                             | 33  | 9,0  | 20                                 |
| 6018-40        | 26 ÷ 30   | M40x1,5 | 45                             | 42  | 10,2 | 25                                 |
| 6018-50        | 39 ÷ 41   | M50x1,5 | 57                             | 54  | 10,0 | 25                                 |
| 6018-63        | 43 ÷ 45   | M63x1,5 | 64                             | 60  | 12,0 | 20                                 |

## Filettatura PG PG thread

| CODICE<br>CODE | SERRAGGIO CAVO<br>CABLE TIGHTENING<br>Ø Min - Ø Max | F    | DIMENSIONI mm<br>DIMENSIONS mm |     | LF   | CONFEZIONE<br>PACKAGE<br>pz / pcs. |
|----------------|---|------|--------------------------------|-----|------|------------------------------------|
|                |   |      | CH1                            | CH2 |      |                                    |
| 6018-07        | 5 ÷ 7   | 7    | 14                             | 13  | 5,0  | 10                                 |
| 6018-09        | 6 ÷ 8   | 9    | 17                             | 15  | 6,0  | 10                                 |
| 6018-11        | 8 ÷ 10  | 11   | 20                             | 18  | 6,0  | 10                                 |
| 6018-13        | 10 ÷ 12   | 13,5 | 22                             | 20  | 6,5  | 10                                 |
| 6018-15        | 12 ÷ 14   | 16   | 24                             | 22  | 6,5  | 10                                 |
| 6018-21        | 15 ÷ 17   | 21   | 30                             | 28  | 7,0  | 10                                 |
| 6018-29        | 24 ÷ 26   | 29   | 40                             | 37  | 8,0  | 10                                 |
| 6018-36        | 31 ÷ 35   | 36   | 50                             | 47  | 9,0  | 10                                 |
| 6018-42        | 39 ÷ 41   | 42   | 57                             | 54  | 10,0 | 5                                  |
| 6018-48        | 43 ÷ 45   | 48   | 64                             | 60  | 10,0 | 5                                  |

## Filettatura GAS ISO 228 GAS ISO 228 thread

| CODICE<br>CODE | SERRAGGIO CAVO<br>CABLE TIGHTENING<br>Ø Min - Ø Max | F      | DIMENSIONI mm<br>DIMENSIONS mm |     | LF   | CONFEZIONE<br>PACKAGE<br>pz / pcs. |
|----------------|---|--------|--------------------------------|-----|------|------------------------------------|
|                |   |        | CH1                            | CH2 |      |                                    |
| 6018-14        | 4 ÷ 6   | 1/4"   | 14                             | 13  | 5,0  | 10                                 |
| 6018-38        | 8 ÷ 10  | 3/8"   | 17                             | 15  | 6,0  | 10                                 |
| 6018-12        | 10 ÷ 12   | 1/2"   | 22                             | 20  | 7,0  | 10                                 |
| 6018-34        | 17 ÷ 19   | 3/4"   | 30                             | 28  | 8,5  | 10                                 |
| 6018-01        | 19 ÷ 22   | 1"     | 35                             | 33  | 9,0  | 10                                 |
| 6018-114       | 26 ÷ 30   | 1" 1/4 | 45                             | 42  | 10,2 | 10                                 |
| 6018-112       | 33 ÷ 35   | 1" 1/2 | 50                             | 47  | 12,0 | 10                                 |
| 6018-02        | 43 ÷ 45   | 2"     | 64                             | 60  | 12,0 | 5                                  |