


■ Pressacavo Cable gland

In acciaio inox AISI 316L **6018XX** In stainless steel AISI 316L **6018XX**



Prodotti in acciaio inox AISI 316L (X2CrNiMo17-12-2 1.4404 UNI EN 10088-1). Il serraggio del dado provoca la deformazione della guarnizione che, oltre a garantire una tenuta stagna IP68 a 5 bar di pressione, assicura una eccezionale tenuta allo strappo. Un'ulteriore guarnizione o-ring alloggiata in apposita sede sagomata, mantiene il grado di tenuta stagna anche sulla filettatura. Presentano un'ottima resistenza alla corrosione. La filettatura è metrica ISO in conformità alle norme CEI EN 60423. Dimensioni ridotte

- Standard **CEI EN 62444**
- Grado di protezione del sistema **IP 68**

Made of stainless steel AISI 316L (X2CrNiMo17-12-2 1.4404 UNI EN 10088-1). The tightening of the nut causes the deformation of the gasket which, besides ensuring a hermetic IP68 seal at 5 bar pressure, ensures an exceptional tearing resistance. A further o-ring gasket housed in a suitable shaped housing, maintains the degree of tightness even on the thread. They have an excellent resistance to corrosion. The ISO metric thread is in compliance with standards IEC EN 60423. Small size

- Standard **IEC EN 50262**
- System protection degree **IP68**

Filettatura Metrica Metric thread

CODICE CODE	SERRAGGIO CAVO CABLE TIGHTENING		DIMENSIONI mm DIMENSIONS mm			CONFEZIONE PACKAGE pz / pcs.
	Ø Min - Ø Max	F	CH1	CH2	LF	
6018XX-M1216	5 ÷ 9	M12x1,5	20	20	10	25
6018XX-M16	5 ÷ 9	M16x1,5	20	20	10	25
6018XX-M1620	8 ÷ 12	M16x1,5	24	24	10	20
6018XX-M20	8 ÷ 12	M20x1,5	24	24	10	20
6018XX-M2025	11 ÷ 16	M20x1,5	30	30	10	15
6018XX-M25	11 ÷ 16	M25x1,5	30	30	10	15
6018XX-M2532	15 ÷ 21	M25x1,5	36	36	10	10
6018XX-M32	15 ÷ 21	M32x1,5	36	36	10	10
6018XX-M3240	20 ÷ 27	M32x1,5	46	46	10	10
6018XX-M40	20 ÷ 27	M40x1,5	46	46	12	10