



## ■ Guarnizione Gasket

In fibra **6060**

In fibre **6060**



Realizzate in fibra di cellulosa con legante elastomerico (esente Amianto), presentano buona resistenza meccanica e termica. Per impieghi a contatto con carburanti, olii animali e vegetali, lubrificanti e gas.



Made of cellulose fibre with elastomeric binder (asbestos-free), with good mechanical and thermal resistance. Suitable for use in contact with fuels, animal and vegetable oils, lubricants and gas.

CODICE CODE	GAS	FILETTO THREAD		DIMENSIONI mm DIMENSIONS mm			CONFEZIONE PACKAGE pz / pcs.
		PG	Metrico Metric	Ø d	Ø D	A	
6060-1319	1/4"	7	-	13,0	19,5	1,8	100
6060-1522	-	9	M16	16,0	22,0	1,8	100
6060-1722	3/8"	-	-	16,5	22,5	1,8	100
6060-1925	-	11	M20	20,0	26,0	1,8	100
6060-2127	1/2"	13,5	-	21,0	27,0	1,8	100
6060-2228	-	16	-	22,5	29,0	1,8	100
6060-2532	-	-	M25	25,0	32,0	1,8	100
6060-2632	3/4"	-	-	26,3	32,5	1,8	100
6060-2834	-	21	-	28,3	34,5	1,8	100
6060-3238	-	-	M32	32,0	38,5	1,8	100
6060-3340	1"	-	-	33,2	40,0	1,8	100
6060-3742	-	29	-	37,6	43,5	1,8	100
6060-4050	-	-	M40	40,0	50,0	1,8	50
6060-4249	1" 1/4	-	-	42,0	49,0	1,8	50
6060-4956	1" 1/2	36	-	47,8	56,5	1,8	50
6060-5060	-	-	M50	50,0	59,5	1,8	25
6060-6070	2"	48	-	60,0	70,0	1,8	25
6060-6472	-	-	M63	63,0	72,0	1,8	25
6060-212*	2" 1/2	-	M75	75,2	86,0	1,8	10
6060-03*	3"	-	-	87,8	97,0	1,8	10
6060-04*	4"	-	-	113,0	124,0	1,8	10

\*A richiesta / On request

In poliammide **6060PA**

In polyamide **6060PA**



Realizzate in poliammide PA6 naturale, presentano elevata resistenza all'abrasione ed ottima resistenza meccanica. Autoestinguenti e prive di sostanze alogene, silicone e cadmio, presentano alta resistenza agli oli e benzine, in particolare ad acidi e solventi.

Made of natural PA6 polyamide, with high resistance to abrasion and excellent mechanical resistance. Self-extinguishing and free of halogen, silicone and cadmium, with high resistance to oils and fuel, in particular to acids and solvents.

CODICE CODE	FILETTO THREAD Metrico Metric	DIMENSIONI mm DIMENSIONS mm			CONFEZIONE PACKAGE pz / pcs.
		Ø d	Ø D	S	
6060PA1622	M16	16	22	1,5	100
6060PA2026	M20	20	26	1,5	100
6060PA2532	M25	25	32	1,5	100
6060PA3239	M32	32	39	1,5	100
6060PA4048	M40	40	48	1,5	50
6060PA5060	M50	50	60	1,5	25