



■ Raccordi a innesto rapido Quick coupling fittings

Tubo rigido - tubo flessibile in ottone nichelato **6117**

Rigid conduit-flexible conduits fittings in nickel plated brass **6117**



**IP66
IP68
IP69**

CODICE CODE	TUBO CONDUIT	TUBO FLESSIBILE FLEXIBLE CONDUIT	ØPU	DIMENSIONI mm DIMENSIONS mm			CONFEZIONE PACKAGE pz / pcs.
	ØD mm	Ød mm		CH	CH2	D	
6117-10N	16	10	8,5	24	24	27	25
6117-12N	16	12	10,0	26	24	29	25
6117-16N	16	16	13,8	30	28	33	25
6117-20N	20	16	13,8	30	28	33	25
6117-2020	20	21	18,0	37	35	40	15
6117-25N	25	21	18,0	37	35	40	15
6117-2527	25	27	23,0	45	42	50	10
6117-32N	32	27	24,0	45	42	50	10
6117-3235	32	35	30,0	52	50	55	5
6117-40	40	40	38,0	61	58	64	5
6117-4035	40	35	32,0	52	58	55	5
6117-5040	50	40	38,0	61	58	64	5
6117-50	50	51	48,0	74	70	78	5
6117-63N	63	51	48,0	74	Ø75	78	1
6117-75*	75	63	59,5	94	94	100	1

* Soluzione con sistema di bloccaggio a vite **SENZA CERTIFICAZIONI**
* Solution with screw locking system **WITHOUT CERTIFICATIONS**

CEI EN 61386



CEI EN 61386

