

■ Casse CE CE boxes

Doppia anta Double door



IP55
TYPE 12

Struttura

lamiera d'acciaio sp. 15/10 verniciata RAL 7035 bucciato.

Pannello di cablaggio

lamiera d'acciaio sp. 20/10 zincato.

Porta in due meta'

reversibile, verniciata RAL 7035 bucciato con guarnizione in colata continua.

Grado di resistenza all'urto secondo IEC EN 62208: IK10

Piastra d'ingresso cavi

posta sul fondo della cassa adeguatamente dimensionata.

Composizione

Struttura, pannello di cablaggio, porta, piastra di ingresso cavi, confezione di viteria.

Structure

15/10 thick steel sheet, painted textured RAL 7035.

Mounting panel

20/10 thick galvanized steel.

Door in two half

reversible, painted textured RAL 7035, provided with a gasket applied in continuous casting

Impact resistance degree as per IEC EN 62208: IK10

Cable gland plate

Appropriately dimensioned and located on the box bottom.

Composition

Structure, mounting panel, door, cable gland plate, set of fasteners.


CODICE CODE	ALTEZZA, H HEIGHT, H	DIMENSIONE DIMENSIONS		CHIUSURA LOCKING ELEMENT
		LARGHEZZA, L WIDTH, L	PROFONDITÀ, P DEPTH, P	
R5CE0683		800		
R5CE0613	600	1000	300	
R5CE06123		1200		
R5CE0812			200	N. 2 Box
R5CE0813	800	1000		
R5CE08123		1200		
R5CE1013	1000			
R5CE1213	1200	1000	300	Cariglione / Ratchet
R5CE1413	1400			
R5CE12123	1200	1200		

■ Casse CE


CE boxes

Doppia anta


Double door




Vista fronte cassa con porta
Box front view with door




Vista fronte cassa senza porta
Box front view without door





Vista retro cassa
Back view



Vista interno porta sinistra
Left internal door view



Vista interno porta destra
Right internal door view



Vista pannello di cablaggio
Wiring panel view

