


CONDIZIONATORI DA PARETE OUTDOOR PER AMBIENTI GRAVOSI WALL MOUNTED OUTDOOR COOLERS FOR HARSH ENVIRONMENTS


 1500W
1500W


Descrizione Description

- Tutte le versioni bifase e trifase possono essere alimentate a differenti tensioni, mediante la modifica del cablaggio interno (seguire schemi).
 - Campo regolazione temperatura (set di fabbrica) da / a: **+30°C / +40°C**
 - Livello di rumore **69 dB (A)**
 - Tipo di refrigerante: In corso la sostituzione del gas attuale **R134a** con il nuovo gas **R513a**.
 - Tipo ciclo di lavoro **100%**
- Opzionale**
COLORE SPECIALE = R9CND...
COVER FRONTALE AISI 316 = RI6CND...

- All two-phase and three-phase versions can be supplied with different voltages, by changing the internal wiring (follow diagrams).
 - Temperature regulating range (factory set) from /to **+30°C / +40°C**
 - Noise level **69 dB (A)**
 - Coolant type: on course to replace the current gas **R134a** with the new **R513a** gas.
 - Operating cycle type **100%**
- Optional**
SPECIAL COLOR = R9CND...
AISI INOX 316 FRONT COVER = RI6CND...

IP55



Dati Tecnici Technical Data

COVER VERNICIATA/PAINTED





CODICE CODE	VERSIONE VERSION	TENSIONE ALIMENTAZIONE POWER SUPPLY	FREQUENZA FREQUENCY HZ	POTENZA FRIGORIFERA (DIN 3168,W) REFRIGERATING POWER (DIN_3168,W)		POTENZA ASSORBITA POWER CONSUMPTION		FLA MASSIMA CORRENTE DI ESERCIZIO FLA MAXIMUM OPERATING CURRENT	CORRENTE DI SPUNTO STARTING CURRENT	PESO WEIGHT KG
				L35/L35	L35/L50	L35/L35	L35/L50			
R5CND15021LOH	-	230 Vac - 1ph	50/60	1500 / 1550	1160 / 1190	700/780	900/980	5,7 / 6,2	28 A	65
R5CND15042LOH	-	400 Vac - 2ph	50/60	1500/1550	1160/1190	700/800	900/980	3,3 / 3,6	16 A	65

COVER INOX/AISI 304

CODICE CODE	VERSIONE VERSION	TENSIONE ALIMENTAZIONE POWER SUPPLY	FREQUENZA FREQUENCY HZ	POTENZA FRIGORIFERA (DIN 3168,W) REFRIGERATING POWER (DIN_3168,W)		POTENZA ASSORBITA POWER CONSUMPTION		FLA MASSIMA CORRENTE DI ESERCIZIO FLA MAXIMUM OPERATING CURRENT	CORRENTE DI SPUNTO STARTING CURRENT	PESO WEIGHT KG
				L35/L35	L35/L50	L35/L35	L35/L50			
RI6CND15021LOH	-	230 Vac - 1ph	50/60	1500 / 1550	1160 / 1190	700/780	900/980	5,7 / 6,2	28 A	65
RI6CND15042LOH	-	400 Vac - 2ph	50/60	1500/1550	1160/1190	700/800	900/980	3,3 / 3,6	16 A	65

1500W
1500W

Specifiche tecniche Technical Specs




1500W
1500W

Specifiche tecniche Technical Specs

Potenza frigorifera
Refrigeration power

W 50Hz



W 60Hz

