

CONDIZIONATORI DA TETTO INDOOR ROOF MOUNTED INDOOR COOLERS

 800W
800W


Descrizione Description



- Tutte le versioni bifase e trifase possono essere alimentate a differenti tensioni, mediante la modifica del cablaggio interno (seguire schemi).
 - Campo regolazione temperatura (set di fabbrica) da / a: **+30°C / +40°C**
 - Livello di rumore **69 dB (A)**
 - Tipo di refrigerante **R134a**. In via di definizione la sostituzione del gas attuale con il nuovo gas **R513a**.
 - Tipo ciclo di lavoro **100%**
- Opzionale
COLORE SPECIALE = R9CND...
COVER FRONTALE AISI 316 = RI6CND..

- All two-phase and three-phase versions can be supplied with different voltages, by changing the internal wiring (follow diagrams).
 - Temperature regulating range (factory set) from /to **+30°C / +40°C**
 - Noise level **69 dB (A)**
 - Coolant type: on course to replace the current gas R134a with the new R513a gas.
 - Operating cycle type **100%**
- Optional
SPECIAL COLOR = R9CND...
AISII INOX 316 FRONT COVER = RI6CND...

IP54



Dati Tecnici Technical Data

COVER VERNICIATA/PAINTED





CODICE CODE	VERSIONE VERSION	TENSIONE ALIMENTAZIONE POWER SUPPLY	FREQUENZA FREQUENCY HZ	POTENZA FRIGORIFERA (DIN 3168,W) REFRIGERATING POWER (DIN 3168,W)		DISPOSITIVO DI PROTEZIONE E SICUREZZA SUGGERITO SUGGESTED PROTECTION AND SAFETY DEVICE	POTENZA ASSORBITA POWER CONSUMPTION		FLA MASSIMA CORRENTE DI ESERCIZIO FLA MAXIMUM OPERATING CURRENT	CORRENTE DI SPUNTO STARTING CURRENT	PESO WEIGHT KG
				L35/L35	L35/L50		L35/L35	L35/L50			
R5CND08021RT	TOP	230 Vac - 1 ph	50/60	860 / 940	690 / 720	6 A	400/460	450/540	2,9 / 3,2	17 A	43
R5CND08042RT	TOP	400 Vac - 2 ph	50/60	830 / 900	650 / 690	4 A	400/460	450/540	1,7 / 1,9	9 A	45

COVER INOX/AISI 304

CODICE CODE	VERSIONE VERSION	TENSIONE ALIMENTAZIONE POWER SUPPLY	FREQUENZA FREQUENCY HZ	POTENZA FRIGORIFERA (DIN 3168,W) REFRIGERATING POWER (DIN 3168,W)		DISPOSITIVO DI PROTEZIONE E SICUREZZA SUGGERITO SUGGESTED PROTECTION AND SAFETY DEVICE	POTENZA ASSORBITA POWER CONSUMPTION		FLA MASSIMA CORRENTE DI ESERCIZIO FLA MAXIMUM OPERATING CURRENT	CORRENTE DI SPUNTO STARTING CURRENT	PESO WEIGHT KG
				L35/L35	L35/L50		L35/L35	L35/L50			
RICND08021RT	TOP	230 Vac - 1 ph	50/60	860 / 940	690 / 720	6 A	400/460	450/540	2,9 / 3,2	17 A	43
RICND08042RT	TOP	400 Vac - 2 ph	50/60	830 / 900	650 / 690	4 A	400/460	450/540	1,7 / 1,9	9 A	45

800W
800W

Specifiche tecniche Technical Specs




800W
800W

Specifiche tecniche Technical Specs

Potenza frigorifera
Refrigeration power

W 50Hz



W 60Hz

